

Thickness	Min. Tolerance	Max. Tolerance	Tolerance
1.00	1.00	1.30	+0.30
2.00	2.00	2.30	+0.30
3.00	3.00	3.30	+0.30
4.00	4.00	4.30	+0.30
5.00	5.00	5.30	+0.30
6.00	6.00	6.30	+0.30
8.00	8.00	8.30	+0.30
10.00	10.00	10.30	+0.30
12.00	12.00	12.30	+0.30
15.00	15.00	15.30	+0.30
20.00	20.00	20.30	+0.30
25.00	25.00	25.30	+0.30
30.00	30.00	30.30	+0.30
35.00	35.00	35.30	+0.30
40.00	40.00	40.30	+0.30
50.00	50.00	50.30	+0.30

Different thickness tolerances on HMPE-500, 2 to 12 mm thick due to production method (extruded).

Thickness	Min. Tolerance	Max. Tolerance	Tolerance
2.00	1.86	2.14	+/- 0.14
3.00	2.83	3.17	+/- 0.17
4.00	3.80	4.20	+/- 0.20
5.00	4.77	5.23	+/- 0.23
6.00	5.74	6.26	+/- 0.26
8.00	7.68	8.32	+/- 0.32
10.00	9.62	10.38	+/- 0.38
12.00	11.56	12.44	+/- 0.44

All dimensions are in millimeters (mm)